

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

1. (original): A refrigerator comprising a main body formed with a storage compartment, a door hingedly connected to the main body; and at least one shelf provided inside the storage compartment,

the shelf comprising:

a glass on which foodstuffs are laid;

a glass supporter coupled to edges of the glass;

a pair of supporting brackets provided in opposite sides of the glass supporter and supported onto a wall of the storage compartment; and

a coupler coupling the glass supporter with the supporting bracket.

2. (currently amended): The refrigerator according to claim 1, wherein the ~~coupler~~ comprises a screw, supporting bracket is coupled to a lower part of the glass supporter.

3. (currently amended): The refrigerator according to claim ~~2~~ 1, wherein the glass supporter comprises a main portion coupled to the edges of the glass; and a bracket ~~coupling~~

~~portion supporter~~ extended downward at opposite sides of the main portion and ~~formed~~
~~supported~~ with a plurality of coupling bosses, and ~~the supporting bracket.~~

~~the supporting bracket is formed with a screw through hole through which the screw is~~
~~coupled to each coupling boss.~~

4. (currently amended): The refrigerator according to claim 3, further comprising a
plurality of coupling bosses formed at the bracket supporter, and wherein the supporting bracket
is formed with a penetrating hole in a position corresponding to each boss, and

the coupler comprises a plurality of screws penetrating the penetrating hole and
accommodated in the coupling boss.~~The refrigerator according to claim 3, wherein the bracket~~
~~coupling portion comprises a plurality of~~

~~supporting ribs formed between the coupling bosses, and~~
~~the supporting bracket is formed with a bending portion fitted to the supporting ribs and~~
~~supporting the main portion.~~

5. (new): The refrigerator according to claim 4, wherein the bracket supporter is
provided with a plurality of supporting ribs formed between the coupling bosses, and the
supporting bracket is provided with a bending portion fitted to the supporting ribs and supporting
the main portion.

6. (new): The refrigerator according to claim 3, wherein the bracket supporter is
provided with a plurality of supporting ribs projected toward the supporting bracket, and the

supporting bracket is provided with a bending portion fitted to the supporting ribs and supporting the main portion.

7. (new): The refrigerator according to claim 1, wherein the storage compartment has a plurality of interval adjusting holes disposed at a side of an inner wall, the refrigerator further comprising a hook portion provided in at least one of the supporting bracket and the glass supporter and selectively coupled to one of the plurality of the interval adjusting holes.